

DH-FACE302 متعددة البيومترية ومحطة التحكم في الوصول T&A

ZKTeco uFace302 Access Control Terminal
 . 10000 4000 3000
 ZKTeco
 .



معامل

RAM	4-3 GB DDR3 SDRAM
Storage Capacity	3000
Fingerprint	4000
IC Card	10000
Barcode	100000
Connectivity	TCP / IP or RS232 / 485 or USB
Operating System	It supports up to 3 operating systems. The operating system is Windows XP, Windows 7, or Windows 10. The operating system is Windows XP, Windows 7, or Windows 10. The operating system is Windows XP, Windows 7, or Windows 10. T9 or 10. The operating system is Windows XP, Windows 7, or Windows 10. 9
Power Supply	Power supply is 100-240V AC, 50/60Hz. Power supply is 100-240V AC, 50/60Hz. Power supply is 100-240V AC, 50/60Hz. Power supply is 100-240V AC, 50/60Hz. Power supply is 100-240V AC, 50/60Hz.
Dimensions	Dimensions:

□□□□□□□ □□□□	□□□□ ID / MiFare □ □□□ Wi-Fi □ 3G □ ADMS □ 2000 □□□□□□□ □□□□□ □□□□□ □ □□□□ □□□□
□□□□□ □□□□	12V 3A
□□□□□□ □□□□ □□□□	0 □□□□□ □□□□ 45 - □□□□□ □□□□
□□□□□□ □□□□□	20□ -80□
□□□□□□□	193.6 * 165.2 * 86 □□□□□□□ * □□□□□ * □□□□□□) □□□□)
□□□□□□□ □□□ □□□□□□□□ □□□	1.6KG