



Função:

A. fechamento automático;

A velocidade de fechamento pode ser ajustada;

C. algumas portas mais próximas têm a função de ficar.

PRODUCT DETAILS SHOW

1 STRETCHABLE MECHANIC ARM

Mechanic Arm can be adjustable,stretchable,even when doorframe and door are not in same plane, it is still able to be installed,satisfying your multiple requirements



2 FASTENED RIVETS

Fastening Rivets assure stability in connection, effective solution in usage and safety, premium performance in wearproof



3 MAIN BODY

Special Structure Design For Components,Multi-Step Processes For Manufacturing,Pass 100000 Times Test,Premium&Durable



4 POLE&BEARING

Special Structure Design For Components, Multi-Step Processes For Manufacturing, Pass 100000 Times Test,Premium&Durable



Vantagem:

O fecho da porta é instalado na parte superior da folha da porta com abertura única, é aplicável à porta de madeira, porta de aço e porta corta-fogo.

Aplicável a uma porta com largura máxima de 950 mm e peso de porta de 35 a 65 kg.

01

CONFIRM TYPE OF DOOR BEFORE INSTALLATION



SUITABLE FOR THESE DOORS

Wooden Door, Aluminum Door, Stainless Steel Door, Iron Door,
Fireproof Door, Anti-Theft Door, Hollow Metal Door etc.
Could be installed on the right or left



Fireproof Door



Wooden Door




Metal Door



Anti-Theft Door


02

ASSURE DOOR AND DOORFRAME ARE ON THE SAME PLANE



DOOR AND DOORFRAME ARE ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe are on the same plane, then door closer will work



DOOR AND DOORFRAME ARE NOT ON THE SAME PLANE

Whatever you use it on inward or outward door, just make sure door and doorframe are on the same plane, then door closer will work